



## Product Data Sheet



# Anti-Spatter Lanolin Based

- FEATURES:**
- Biodegradable
  - Non-toxic
  - Non-carcinogenic
  - Non-flammable
  - No Methylene Chloride
  - No silicones

- PACK SIZES:**
- 750ml Spray Pack
  - 5 Litre Jerry Can

### USES:

- Welding anti-spatter for mig and arc welding
- Corrosion inhibitor
- Lubricant for tapping and pressing
- Excels as an aid for drilling stainless steel and alloys

### CONTENTS:

Lanolin, blended with non-regulated paraffinic carrier(s) to enable ease of application. Product may also contain natural masking agent(s) and/or other additives to reduce odour.

### PHYSICAL PROPERTIES:

- Appearance: Light brown liquid with distinctive wool fleece and solvent odour.
- Boiling Point: Not Determined
- Flash Point: > 110°C
- Specific Gravity: 0.81 - 0.83 @ 24°C
- Solubility in Water: Very Low

### APPLICATION GUIDE:

- For the best results with Lanotec Anti-Spatter hold the can approximately 30 cm from the surface and apply a thin coat of Anti-Spatter to the surrounding weld area where spatter may stick.
- Only a mist spray is required compared to conventional anti-spatters
- Tests have shown that spraying directly into the weld area will not cause weld defects such as porosity.

### CONTACT DETAILS FOR FURTHER INFORMATION:

Lanotec Australia Pty Ltd

Phone: 07 3373 3700

Email: [info@lanotec.com.au](mailto:info@lanotec.com.au)

Fax: 07 3373 3777

Web: [www.lanotec.com.au](http://www.lanotec.com.au)

# NATURALLY BETTER