



Product Data Sheet

General Purpose Liquid Lanolin



- FEATURES:**
- Long Term Biodegradable
 - Non-toxic • Non-carcinogenic
 - Non-evaporative
 - Non-leaching
 - Hermetically seals surfaces
 - Non-Perishing • Pro-active
 - Non-conductive to 70kV
 - Good resistance to mineral acids

- PACK SIZES:**
- 400g Aerosol
 - 750ml Spray Pack
 - 1 Litre Jerry Can
 - 5 Litre Jerry Can
 - 20 Litre Drum

USES:

- Electrical component protection — Non Conductive to 70Kv
- Protection of electrical connectors, switchgear, ECU's and circuit boards
- Internal component preservation
- Vehicle rust protection
- Protection inside Air Conditioning units
- Protects and frees up tools, fasteners, fittings, hinges, locks and zippers
- Protection inside cowlings, over power heads and fishing equipment
- Protection of electric motors, alternators and generators
- Rejuvenates plastics, vinyls and aluminium
- Waterproofs and rejuvenates leather

CONTENTS:

Lanolin, blended with non-regulated, non-ozone depleting paraffin carrier's to enable ease of application and enhance penetration.

PHYSICAL PROPERTIES:

- Appearance: Light brown liquid with distinctive wool fleece and solvent odour.
- Boiling Point: Approx. 110-200°C
- Flash Point: > 82°C
- Specific Gravity: 0.81 - 0.83 @ 24°C
- Solubility in Water: Insoluble

CONTACT DETAILS FOR FURTHER INFORMATION:

Lanotec Australia Pty Ltd

Phone: 07 3373 3700

Email: info@lanotec.com.au

Fax: 07 3373 3777

Web: www.lanotec.com.au

NATURALLY BETTER