



Product Data Sheet



Type 'A' Grease

- FEATURES:**
- Long Term biodegradable
 - Non-toxic
 - Non-carcinogenic
 - Non-evaporative
 - Non-leaching
 - Acid & salt resistant
 - Pro-active
 - Non-conductive to 70kV
 - Non-perishing to rubber O rings and seals

- PACK SIZES:**
- 235ml Tub
 - 250ml Tube
 - 500ml Tub
 - 1 Litre Tub
 - 4 Litre Tub
 - 20 Litre Drum

USES:

- Type 'A' Grease is certified as Food Grade and is non conductive to 70kV
- Welding nozzle dip
- Drilling and cutting aid
- Prevents galling of stainless steel and aluminium
- Anti-seize for threaded rod, nuts and bolts
- Stops electrolysis due to dissimilar metals
- Metal to metal soft seal gasket
- Lubricant for rubber hoses, linkages, pivot pins and bushes
- Corrosion and moisture proofing for multi-pin connectors
- Belt Grip

CONTENTS:

Type 'A' Grease is pure Lanolin.

PHYSICAL PROPERTIES:

- Appearance: Light brown coloured solid
- Boiling Point: Approx. 120-140°C
- Flash Point: 158°C
- Specific Gravity: 0.92 @ 24°C
- Solubility in Water: Insoluble

CONTACT DETAILS FOR FURTHER INFORMATION:

Lanotec Australia Pty Ltd
Phone: 07 3373 3700
Email: info@lanotec.com.au

Fax: 07 3373 3777
Web: www.lanotec.com.au

NATURALLY BETTER