



## Product Data Sheet



## Lanotec U.P.

- FEATURES:**
- Long Term Biodegradable
  - Non-toxic
  - Non-carcinogenic
  - Non-evaporative
  - Non-leaching
  - Hermetically seals surfaces
  - Pro-active
  - Good resistance to mineral acids/salt

- PACK SIZES:**
- 750ml Spray Pack
  - 5 Litre Jerry Can
  - 20 Litre Drum

### USES:

- The Ultimate in corrosion Protection.
- Corrosion protection in harsh and highly corrosive environments.
- Machinery, Equipment, Internal Shed walls and Outside storage protection (Eg Fertilizer sheds, tanneries, voids of ships etc.)

### CONTENTS:

Enhanced Lanolin blended with an evaporative carrier to enable ease of application.

### PHYSICAL PROPERTIES:

- Appearance: Dark brown liquid with distinctive wool fleece odour.
- Boiling Point: Approx. 100-200°C
- Flash Point: 63°C
- Specific Gravity: 0.85
- Solubility in Water: Insoluble

### APPLICATION GUIDE:

- For the best results Lanotec U.P. should be applied to clean, dry surfaces by spray or lambs wool applicator. Loose and flaking rust/paint must be removed prior to application. Apply in a well ventilated area and allow sufficient time for the carrier to evaporate before using coated items.

### CONTACT DETAILS FOR FURTHER INFORMATION:

Lanotec Australia Pty Ltd  
Phone: 07 3373 3700  
Email: [info@lanotec.com.au](mailto:info@lanotec.com.au)

Fax: 07 3373 3777  
Web: [www.lanotec.com.au](http://www.lanotec.com.au)

# NATURALLY BETTER