

Always read entire label before using product



- FEATURES:**
- Non Flammable
  - Does not affect galvanising process
  - Ideal for confined spaces
  - No Methylene Chloride
  - Versatile & Safe

**CONTENTS:** Lanolin (a natural product), blended with an evaporative carrier to enable ease of application and enhance penetration

## USAGE EXAMPLES:

- Welding anti-spatter for mig and arc welding
- Lubricant for cutting, tapping, drilling and pressing
- Corrosion and spatter protection of welding beds, robots and spot welders
- Can be used to protect and prolong the life of welding gloves and aprons
- Welding nozzle protection

## STORAGE & TRANSPORT:

- Aerosols classified as Dangerous Goods for transport and storage (UN 1950; DG 2.1 2YE)
- All other sizes are not classified as DG
- Keep in cool, dry, well ventilated place
- Keep out of reach of children
- Shelf life - virtually indefinite if kept sealed in reasonable conditions



## PREPARATION:

- Best applied to dry, clean surfaces
- Anti-Spatter (AS) can be sprayed to corrosive surfaces to stop further corrosion

## APPLICATION:

- Shake container to ensure product is mixed correctly. Colder climates will require extra agitation.
- Lanotec Anti-Spatter can be applied via spray

## REMOVAL:

- Lanotec recommends the use of Lanotec Citra-Force™ or Lanotec PowaWash™.

## TESTING:

- Test welds meet Standard AS/NZS 1554.1 2004 Category SP