



Penetrant | Lubricant

Always read entire label before using product

- FEATURES:**
- Lubricates
  - Penetrates
  - Resistant to acids and salts
  - Resists wash off
  - Non conductive to 70kV
  - Food Grade
  - Non flammable
  - Biodegradable

**CONTENTS:** Lanolin (a natural product), blended with an evaporative carrier to enable ease of application and penetration

### USAGE EXAMPLES:

- Lubricates
  - o Cable and pulling lube
  - o Cabinet hinges
  - o Escalator components
  - o Automatic motor components and electrics
- Spray on long-term corrosion protection for:
  - o Electronic components (non-conductive to 70kV)
  - o Circuit boards, connectors & terminals, cables, air-con units, compressors
- Spray on anti-seize for locks, nuts and bolts
- Penetrates, lubricates and protects wire ropes
- Resists wash-off
- Moisture protection for electrical components
- Dielectric to 70 kV
- Contains no silicones
- Safe on rubber and plastics
- Salt spray tested to AS2331.3.1
- Corrosion & moisture protection for internals of electrical cabinets & battery terminals

### STORAGE & TRANSPORT:

- Aerosols classified as Dangerous Goods (pressurised container, non-flammable) for transport and storage (UN 1950; DG 2.2 2YE)
- All other sizes are classified as NON DG
- Keep in cool, dry, well ventilated place
- Keep out of reach of children

### PREPARATION:

- Best applied to dry, clean surfaces

### APPLICATION:

- Shake container to ensure product is mixed correctly. Colder climates will require extra agitation.
- Lanotec EGX can be applied via spray, brush or roller.
- Allow approximately one hour before any equipment is subject to water

### CERTIFICATION:

- HACCP - Food Grade
- Salt Spray Test - AS2331.3.1 & MIL-C-16173 (Class II Grade 2 or 3)
- Global Green Tag - Sustainability
- NSF
- Made in Australia

**Note:** This product has been classified as supplied. When used as directed, and the volatile substances have completely evaporated, the residue is non hazardous (non combustible). Refer to SDS for Lanotec Type A Grease for safety guidance on expected product residual.

FOR MORE INFORMATION: Lanotec Australia Pty Ltd  
PO Box 360 Archerfield QLD 4108 07 3373 3700 info@lanotec.com.au

For safe handling of this product, please consult the Safety Data Sheet (SDS)