

Always read entire label before using product



- FEATURES:**
- Non DG
 - Ready to use
 - Safe on rubbers and polystyrene
 - Non staining
 - Compatible with most coating systems

CONTENTS: Lanolin (a natural product), blended with an evaporative carrier & surfactant. Mixes with water.

USAGE EXAMPLES:

- Concrete release agent for formwork, precast and tilt panel
- For use on form surfaces including steel, timber, plywood, plastic & fibreglass
- Bond breaker
- Excellent performance with specialised and geo-polymer concrete
- Extends the life of timber and metal moulds
- Protection of equipment from concrete and paint overspray
- Can be used to lubricate and protect jacks & fittings
- Safe for environmentally sensitive areas and waterways

STORAGE & TRANSPORT:

- This product is classified as non-Dangerous Goods
- Store in a cool, dry place
- Shelf life is approx. 2 years from manufacture date(See Best Before date label on container)



PREPARATION:

- Shake 20L container before use or decanting
- Agitate 200L drum with mechanical stirrer or air hose system before use or decanting
- Ensure form surface is clean and dry
- Product is ready to use, no dilution is required
- Product can be decanted into spray applicators. Good quality applicators are recommended for a fine, even coverage
- Lano-Form™ can be applied after setting polystyrene block outs

APPLICATION:

- For best results it is recommended that Lano-Form™ be applied by spray application
- Coverage rate is approximately 20-25m² per litre
- Only a very fine mist is required
- For formwork, ensure a light and even coverage. Only one coat is required
- No cleaning required between pours, simply spray, pour, strip and repeat
- When using as a bond breaker, apply to the top of cured panel in 2 even diagonal opposing coats.
- In extreme heat, the panels can be sprayed with water before Lano-Form™ is applied, this reduces the amount of Lano-Form™ absorbed by the cured panel

REMOVAL:

- If using to protect equipment from overspray and you wish to remove; or you simply wish to remove Lano-Form™, use Lanotec Citra-Force™ or Lanotec PowaWash™.

AS4020 Certification - for use in contact with drinking water - testing conducted by NATA certified laboratory

Global Green Tag Certified as a environmentally sustainable product