

Always read entire label before using product



- FEATURES:**
- Lubricates
 - Penetrates
 - Resistant to acids and salts
 - Resists wash off
 - Non conductive to 70kV
 - Food Grade
 - Non flammable
 - Biodegradable

CONTENTS: Lanolin (a natural product), blended with an evaporative carrier to enable ease of application and penetration

USAGE EXAMPLES:

- Highly effective lubricant for:
 - Steering cables, inboard leg, drive shafts, outboard bracket, hinges, chains
- Corrosion protection for:
 - Inboards, outboards, electronics, cables
 - Engine mounts, pumps, chains, moorings
 - Crevice and cavity protection
 - Prevents galling of dissimilar metals
 - Protects wiring connectors (non-conductive to 70kV)
 - Canopy frames & rivets
- Spray on anti-seize for locks, nuts and bolts
- Penetrates, lubricates & protects wire ropes, linkages & shackles, trailers & winches

- Salt spray tested to AS2331.3.1
- Safe on rubber and plastics
- Corrosion & moisture protection for electrical cabinets & battery terminals
- Highly resistant to wash-off
- Works deep into metal surfaces to protect and preserve
- Safe in marine sensitive areas; NSF, HACCP (food Grade), Global Green Tag certification
- Repels moisture with a hermetically sealing barrier
- Retards marine growth
- Protects sensitive communications equipment

STORAGE & TRANSPORT:

- Aerosols classified as Dangerous Goods (pressurised container, non-flammable) for transport and storage (UN 1950; DG 2.2 2YE)
- All other sizes are classified as NON DG
- Keep in cool, dry, well ventilated place
- Keep out of reach of children

PREPARATION:

- Best applied to dry, clean surfaces

APPLICATION:

- Shake container to ensure product is mixed correctly. Colder climates will require extra agitation.
- Lanotec MGX can be applied via spray, brush or roller.
- Allow approximately one hour before any equipment is subject to water

CERTIFICATION:

- HACCP - Food Grade
- Salt Spray Test - AS2331.3.1 & MIL-C-16173 (Class II Grade 2 or 3)
- Global Green Tag - Sustainability
- NSF
- Made in Australia

Note: This product has been classified as supplied. When used as directed, and the volatile substances have completely evaporated, the residue is non hazardous (non combustible). Refer to SDS for Lanotec Type A Grease for safety guidance on expected product residual.