



Always read entire label before using product

- FEATURES:**
- High resistance to acids and salts
  - Resists wash off
  - Non Evaporative

**CONTENTS:** Pentalan™ (a natural product), blended with an evaporative carrier to enable ease of application and enhance penetration

### USAGE EXAMPLES:

- 4WD and Light Vehicle underbody & chassis rails protection
- Protection of all marine hardware including electrical
- Chemical storage facilities and equipment protection
- Agricultural vehicles including boom sprayers & fertilizer spreaders
- Electrical component protection - non conductive to 41kV

### STORAGE & TRANSPORT:

- Aerosols classified as Dangerous Goods for transport and storage (UN 1950; DG 2.1 2YE)
- All other sizes are not classified as DG
- Keep in cool, dry, well ventilated place
- Keep out of reach of children
- Shelf life - virtually indefinite if kept sealed in reasonable conditions



### PREPARATION:

- Best applied to dry, clean surfaces
- U.P. (Ultimate Protection) can be sprayed to corrosive surfaces to stop further corrosion
- Remove sources of ignitions, voltage and flame until solvent evaporates (approximately one hour).

### APPLICATION:

- Shake container to ensure product is mixed correctly. Colder climates will require extra agitation.
- Lanotec U.P. (Ultimate Protection) can be applied via spray, brush or roller.
- Allow approximately one hour before any equipment is subject to water.

**Note:** This product has been classified as supplied. When used as directed, and the volatile substances have completely evaporated, the residue is non hazardous (non combustible). Refer to SDS for Lanotec Type A Grease for safety guidance on expected product residual.

For safe handling of this product, please consult the Safety Data Sheet (SDS)